

Steel fireplace FLOKI L left 12 kW Ø 200

SKU: FLOKI/L/L EAN: 5903751242321



Technical data

General data

Version	Corner left
Rated output (kW)	12
Heating power range (kW)	10-14
Heating efficiency (%)	85
Exhaust gas temperature (°C)	260
Max length of logs (cm)	50
Min inlet grids active field (cm ²)	500
Min outlet grids active field (cm ²)	700
Flue outlet diameter (mm)	200
Color	Black
Self Closure	No
Materials	Steel
Door opening direction	Left

Energetic efficiency

Energy class	A+
Energy efficiency index (EEI)	106
Seasonal Heating efficiency (%)	75
Moc cieplna do ogrzewania pomieszczeń (kW)	12
CO emissions (at 13% O ₂) ≤ given in %	0.1
Emisja CO (mg/m ³)	1146
Dust emission (mg/Nm ³)	17
Emisja NO _x (mg/Nm ³)	106
Emisja OGC (mg/Nm ³)	76
Flue gases mass flow rate (g/s)	9.3

Certifications / Compliance

Meets requirements	Ecodesign, Designed for recuperation, BImSchV 2
--------------------	--

Additional information

Design features	Air intake - built in , Ashpan, Combustion chamber lining, Decorative glass
-----------------	--

Front type	Steel front with painted glass
------------	---------------------------------------

Type of fuel	Seasoned deciduous wood (humidity ≤20%)
--------------	--

EAN	5903751242321
-----	----------------------

Physical parameters

Width (cm)	93
Height (cm)	129.7
Depth (cm)	49.85
Weight (kg)	169.38

