

Steel fireplace MBO 15 kW Ø 200 Lift-up

SKU: MBO/G EAN: 5901350079850



Technical data

General data

Version	Prosty gilotyna
Rated output (kW)	15
Heating power range (kW)	7.0 - 19.0
Heating efficiency (%)	83
Exhaust gas temperature (°C)	240
Max length of logs (cm)	50
Min inlet grids active field (cm ²)	≥700
Min outlet grids active field (cm ²)	≥900
Flue outlet diameter (mm)	200
Color	Black
Self Closure	No
Materials	Steel
Door opening direction	Up

Energetic efficiency

Energy class	A+
Energy efficiency index (EEI)	109.3
Moc cieplna do ogrzewania pomieszczeń (kW)	15
CO emissions (at 13% O ₂) ≤ given in %	0.09
Dust emission (mg/Nm ³)	30

Certifications / Compliance

Meets requirements

**KRATKI PRO, Ecodesign,
Designed for recuperation,
BlmSchV 2**

Additional information

Design features

**Air intake - built in ,
Combustion chamber
lining, Decorative glass**

Front type

**Steel front with painted
glass**

Type of fuel

**Seasoned deciduous wood
(humidity ≤20%)**

EAN

5901350079850

Physical parameters

Width (cm) **95.2**

Height (cm) **144**

Depth (cm) **51.8**

Weight (kg) **305**

