

Steel fireplace MB 20 kW Ø 200 Lift-up

SKU: MB120/G EAN: 5901350079966



Technical data

General data

Version	Prosty gilotyna
Rated output (kW)	20
Heating power range (kW)	10.0 - 27.0
Heating efficiency (%)	80
Exhaust gas temperature (°C)	240
Max length of logs (cm)	50
Min inlet grids active field (cm ²)	≥800
Min outlet grids active field (cm ²)	≥1000
Flue outlet diameter (mm)	200
Color	Black
Self Closure	No
Door opening direction	Up

Energetic efficiency

Energy class	A
Energy efficiency index (EEI)	105.4
Moc cieplna do ogrzewania pomieszczeń (kW)	20
CO emissions (at 13% O ₂) ≤ given in %	0.1
Dust emission (mg/Nm ³)	11

Certifications / Compliance

Meets requirements

**KRATKI PRO, Ecodesign,
Designed for recuperation,
BlmSchV 2**

Additional information

Design features

**Air intake - built in ,
Combustion chamber
lining, Decorative glass**

Front type

**Steel front with painted
glass**

Type of fuel

**Seasoned deciduous wood
(humidity $\leq 20\%$)**

EAN

5901350079966

Physical parameters

Width (cm) **145.4**

Height (cm) **136.3**

Depth (cm) **56**

Weight (kg) **396**

